

## VOLVIK Premium Range

Construction	2-Piece
Diameter	42.80mm ( $\pm 0.05$ )
Weight	45.50g ( $\pm 0.30$ )
Compression	90 ( $\pm 3$ )
Hardness (Shore D)	65 ( $\pm 3.0$ )
Dimple Pattern	392
C.O.R	0.79

## Test Result

\* Temperature: 16°C~17.1°C, Humidity: 38%~41%, Equipment: TRACKMAN

Driver Speed (mph)	Club Speed (mph)	Ball Speed (mph)	Spin Rate (rpm)	Max Height-X (m)	Max Height-Y (m)	Launch Angle (deg)	Land Angle (deg)	Carry (m)	Run (m)	Length (m)	Flight Time (sec)
80	81.0	121.4	2915.0	103.9	25.00	15.1	-45.0	158.8	11.8	170.7	5.83
90	89.6	135.9	2358.9	121.60	22.16	11.8	-36.7	187.96	19.6	207.6	6.00
100	96.0	146.3	2764.0	133.50	27.50	11.2	-45.2	192.4	11.2	203.6	6.44

\* **Warranty, Limited Remedy, and Limitation of Liability:** Volvik premium range data sheet is designed and intended for golf driving range; unless Volvik separately agrees in writing any other use is not recommended or supported. Many factors that are uniquely within user's knowledge and control can affect the use and performance of Volvik premium range balls in a particular application. The user is solely responsible for evaluating the Volvik product and determining whether it is fit for a particular purpose and suitable for the user's process. Volvik makes no other warranties or conditions, express or implied, including, but not limited to, any implied warranty or condition of merchantability or fitness for a particular purpose or any implied warranty or condition arising out of a course of dealing, custom or usage of trade. Except where prohibited by law, Volvik will not be liable for any loss or damage arising from the premium range performance, use or inability to use Volvik products, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.